

溶接管

SUS316L

外径	×	肉厚	×	長さ	規格	仕上
165.2	×	11	×	4000	TP	—
216.3	×	3	×	4000	TP	—
	×	4	×	4000	〃	—
	×	6.5	×	4000	〃	—
	×	8.2	×	4000	〃	—
	×	12.7	×	4000	〃	—
267.4	×	3	×	4000	TP	—
	×	4	×	4000	〃	—
	×	6.5	×	4000	〃	—
	×	9.3	×	4000	〃	—
	×	15.1	×	4000	〃	—
318.5	×	4	×	4000	TP	—
	×	4.5	×	4000	〃	—
	×	6.5	×	4000	〃	—
	×	10.3	×	4000	〃	—
355.6	×	4	×	4000	TPY-SA	—
	×	5	×	4000	〃	—
	×	8	×	4000	〃	—
	×	11.1	×	4000	〃	—
406.4	×	4	×	4000	TPY-SA	—
	×	5	×	4000	〃	—
	×	8	×	4000	〃	—
	×	12.7	×	4000	〃	—
457.2	×	4	×	4000	TPY-SA	—
	×	5	×	4000	〃	—
	×	8	×	4000	〃	—
	×	14.3	×	4000	〃	—
508	×	5	×	4000	TPY-SA	—
	×	9.5	×	4000	〃	—