

# シームレス管 / SUS304

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上
2	0.5	—	2000	0.0187	TP	C
2.5	0.5	—	2000	0.0249	〃	〃
3	0.5	—	2000	0.0311	〃	〃
			4000			
	1	—	2000	0.0498	〃	〃
			4000			
4	0.5	—	2000	0.0436	〃	〃
			4000			
	1	—	2000	0.0747	〃	〃
			4000			
5	0.5	—	2000	0.0560	〃	〃
			4000			
	1	—	2000	0.0996	〃	〃
			4000			
1.5	—	2000	0.131	〃	〃	
		4000				
6	0.5	—	2000	0.0685	〃	〃
			4000			
	0.8	—	4000	0.104	〃	〃
			4000			
	1	—	2000	0.125	〃	〃
			4000			
	1.2	—	4000	0.144	〃	〃
			4000			
1.5	—	2000	0.168	〃	〃	
		4000				
2	—	4000	0.199	〃	〃	
		4000				
6.35	0.5	—	2000	0.0729	〃	〃
			4000			
	1	—	2000	0.133	〃	〃
			4000			
	1.5	—	4000	0.181	〃	〃
4000						
2	—	4000	0.217	〃	〃	
		4000				
7	0.5	—	2000	0.0810	〃	〃
			4000			
	1	—	2000	0.150	〃	〃
			4000			

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上
7	1.5	—	4000	0.206	TP	C
	2	—	4000	0.249	〃	〃
8	0.5	—	2000	0.0934	〃	〃
			4000			
	0.8	—	4000	0.144	〃	〃
			4000			
	1	—	2000	0.174	〃	〃
			4000			
	1.2	—	4000	0.203	〃	〃
			4000			
1.5	—	4000	0.243	〃	〃	
		4000				
2	—	2000	0.299	〃	〃	
		4000				
2.5	—	4000	0.343	〃	〃	
		4000				
9	0.5	—	2000	0.106	〃	〃
			4000			
	1	—	2000	0.199	〃	〃
			4000			
	1.5	—	4000	0.280	〃	〃
			4000			
2	—	4000	0.349	〃	〃	
		4000				
9.53	0.5	—	2000	0.113	〃	〃
			4000			
	1	—	2000	0.213	〃	〃
			4000			
	1.2	—	4000	0.249	〃	〃
4000						
1.5	—	4000	0.300	〃	〃	
		4000				
2	—	4000	0.375	〃	〃	
		4000				
10	0.5	—	2000	0.118	〃	〃
			4000			
	0.8	—	4000	0.183	〃	〃
			4000			
	1	—	2000	0.224	〃	〃
			4000			
1.2	—	4000	0.263	〃	〃	
		4000				
1.5	—	2000	0.318	〃	〃	
		4000				
2	—	2000	0.399	〃	〃	
		4000				

# シームレス管 / SUS304

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上	外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上
10	2	—	4000	0.399	TP	C	12.7	1	—	2000	0.291	TP	C
	2.5	—	4000	4000									
	3	—	4000	0.523				1.2	—	4000	0.344	”	”
10.5 6A 1/8 B	1 (SCH5S)	—	4000	0.237	”	”		1.5	—	4000	0.419	”	”
	1.2 (SCH10S)	—	4000	0.278	”	”		1.65	—	4000	0.454	”	”
	1.5 (SCH20S)	—	4000	0.336	”	”		2	—	4000	0.533	”	”
	1.7 (SCH40)	—	4000	0.373	”	”	13	0.5	—	4000	0.156	”	”
			5500										
	2	—	4000	0.424	”	”		1	—	4000	0.299	”	”
5500													
2.4 (SCH80)	—	4000	0.484	”	”	1.5		—	4000	0.430	”	”	
		5500											
11	0.5	—	4000	0.131	”	”	13.8 8A 1/4 B	1.2 (SCH5S)	—	4000	0.377	”	”
	1	—	4000	0.249	”	”							
	1.5	—	4000	0.355	”	”		1.65 (SCH10S)	—	4000	0.499	”	”
	3	—	4000	0.598	”	”							
12	0.5	—	2000	0.143	”	”	2 (SCH20S)	—	4000	0.588	”	”	
			4000										
	0.8	—	4000	0.223	”	”	2.2 (SCH40)	—	4000	0.636	”	”	
	1	—	2000	0.274	”	”							
	4000												
	1.2	—	4000	0.323	”	”	3 (SCH80)	—	4000	0.807	”	”	
	1.5	—	4000	0.392	”	”							
	2	—	2000	0.498	”	”	14	0.5	—	4000	0.168	”	”
			4000										
	2.5	—	4000	0.592	”	”		1	—	4000	0.324	”	”
4000													
3	—	4000	0.673	”	”	1.5	—	4000	0.467	”	”		
		4000											
12.7	0.5	—	2000	0.152	”	”	2	—	2000	0.598	”	”	
			4000										
	0.8	—	2000	0.237	”	”	3	—	4000	0.822	”	”	
			4000										
15	0.5	—	2000	0.181	”	”	0.5	—	2000	0.349	”	”	
			4000										
	1	—	2000	0.349	”	”							
4000													

# シームレス管 / SUS304

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上
15	1.2	—	4000	0.413	TP	C
	1.5	—	4000	0.504	〃	〃
	2	—	4000	0.648	〃	〃
	3	—	4000	0.897	〃	〃
	4	—	2000 4000	1.10	〃	〃
15.88	1	—	4000	0.371	〃	〃
16	0.5	—	2000	0.193	〃	〃
			4000			
	1	—	4000	0.374	〃	〃
	1.2	—	4000	0.442	〃	〃
	1.5	—	4000	0.542	〃	〃
	1.6	—	4000	0.574	〃	〃
	2	—	2000	0.698	〃	〃
			4000			
	2.5	—	4000	0.841	〃	〃
	3	—	4000	0.972	〃	〃
	3.5	—	4000	1.09	〃	〃
4	—	4000	1.20	〃	〃	
17.3 10A 3/8 B	1.2 (SCH5S)	—	4000	0.481	〃	〃
			5500			
	1.65 (SCH10S)	—	4000	0.643	〃	〃
			5500			
	2 (SCH20S)	—	4000	0.762	〃	〃
			5500			
	2.3 (SCH40)	—	4000	0.859	〃	〃
			5500			
			6000			
	3.2 (SCH80)	—	4000	1.12	〃	〃
			5500			
6000						
4	—	4000	1.33	〃	〃	

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上
18	0.5	—	4000	0.218	TP	C
	1	—	4000	0.424	〃	〃
	1.5	—	4000	0.617	〃	〃
	2	—	4000	0.797	〃	〃
	2.5	—	2000	0.965	〃	〃
			4000			
	3	—	4000	1.12	〃	〃
4	—	4000	1.40	〃	〃	
19	0.5	—	2000	0.230	〃	〃
			4000			
	1	—	4000	0.448	〃	〃
	1.2	—	4000	0.532	〃	〃
	1.5	—	4000	0.654	〃	〃
	1.6	—	4000	0.694	〃	〃
	2	—	4000	0.847	〃	〃
	2.5	—	4000	1.03	〃	〃
	3	—	4000	1.20	〃	〃
	3.5	—	4000	1.35	〃	〃
	4	—	4000	1.49	〃	〃
20	0.5	—	4000	0.243	〃	〃
	1	—	4000	0.473	〃	〃
	1.5	—	4000	0.691	〃	〃
	2	—	4000	0.897	〃	〃
	2.5	—	4000	1.10	〃	〃
	3	—	4000	1.27	〃	〃
	4	—	4000	1.59	〃	〃
21.7 15A 1/2 B	1.2	—	4000	0.613	〃	〃
			5500			
	1.65 (SCH5S)	—	4000	0.824	〃	〃
			5500			
	2.1 (SCH10S)	—	4000	1.03	〃	〃
			5500			
6000						

# シームレス管 / SUS304

15

継目無ステンレス鋼管

SUS304

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上	外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上						
21.7 15A 1/2 B	2.5 (SCH20S)	—	4000	1.20	TP	C	25	5	—	4000	2.49	TP	C						
			5500							4000				2.84	"	"			
			6000					2.8	—	4000	1.32	"	"						
	5500	4000	0.608	"	"														
	6000	1.2				—				4000				0.723	"	"			
	3.7 (SCH80)	—	4000	1.66	"	"		1.5	—	4000	0.893	"	"	"	"				
			5500													1.6	—	4000	0.949
			6000					2	—	4000	1.17	"	"	"	"	"	"	"	"
	5500	3	—	4000	1.67	"				"									
	6000	4.7 (SCH160)	—	4000	1.99	"				"									
	5500			4				—	4000		2.13	"	"						
	5400								5					—	4000	2.54	"	"	
22	1	—	2000	0.523	"	"	26	3	—	4000	1.72	"	"						
			4000							27.2 20A 3/4 B				1.2	—	4000	0.777	"	"
	1.5	—	4000	0.766	"	"		1.65 (SCH5S)	—		4000	1.05	"			"			
	2		—							4000	0.996			"	"		5500	2.1 (SCH10S)	—
	3	—		4000	1.42	"		"	6000	2.5 (SCH20S)		—	4000			1.54			
	4		—	4000							1.79		"	"	5500		2.9 (SCH40)	—	4000
	4.5	—		4000	1.96	"		"	6000	3.9 (SCH80)		—				4000			2.26
23	1		—	4000							0.548		"	"	5000	5.5 (SCH160)	—	4000	
		1.5		—	2000	0.803		"	"	5500		7.8 (XXS)						—	4000
	4000		2		—						4000		1.05	"	"				
24	1	—	4000	0.573	"	"		5500	3.77	"	"	"	"	"					
			2												—	4000	1.05	"	"
25	1	—	2000	0.598	"	"	25.4	1	—	4000	0.608	"	"						
			4000							1.2				—	4000	0.711	"	"	
	1.2	—	4000	0.711	"	"		1.5	—		4000	0.878	"		"				
	1.5		—							4000	0.878			"		"	1.6	—	4000
	2	—		4000	1.15	"		"	1.6	—		4000	0.949		"				"
	2.5		—	4000							1.40	"		"		2	—	4000	
	3	—		4000	1.64	"		"	3	—			4000		1.67			"	"
	3.5		—	4000							1.87	"	"	4		—	4000		
4	—	4000		2.09	"	"	5	—	4000	2.54					"		"		

# シームレス管 / SUS304

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上
28	1	26	4000	0.673	TP	C
	1.5	25	4000	0.990	〃	〃
	2	24	4000	1.30	〃	〃
	3	22	4000	1.87	〃	〃
	6	16	4000	3.29	〃	〃
29	1	27	4000	0.698	〃	〃
30	1	28	4000	0.722	〃	〃
	1.5	27	4000	1.06	〃	〃
	2	26	4000	1.40	〃	〃
	2.5	25	4000	1.71	〃	〃
	3	24	4000	2.02	〃	〃
	3.5	23	4000	2.31	〃	〃
	4	22	4000	2.59	〃	〃
	5	20	4000	3.11	〃	〃
32	1	30	4000	0.772	〃	〃
	1.2	29.6	4000	0.921	〃	〃
	1.5	29	4000	1.14	〃	〃
	2	28	4000	1.49	〃	〃
	3	26	4000	2.17	〃	〃
	4	24	4000	2.79	〃	〃
	5	22	4000	3.36	〃	〃
	6	20	4000	3.89	〃	〃
	8	16	4000	4.78	〃	〃
34 25A 1B	1.2	31.6	4000	0.981	〃	〃
	1.65 (SCH5S)	30.7	4000	1.33	〃	〃
			5500			
	2	30	4000	1.59	〃	〃
	2.8 (SCH10S)	28.4	4000	2.18	〃	H
			5500			
			6000			
	3 (SCH20S)	28	4000	2.32	〃	〃
			5500			
			6000			

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上
34 25A 1B	3.4 (SCH40)	27.2	4000	2.59	TP	C/H
			5500			
			6000			
	4.5 (SCH80)	25	4000	3.31	〃	〃
			5500			
			6000			
	5	24	4000	3.61	〃	H
			5000			
	6.4 (SCH160)	21.2	4000	4.40	〃	C/H
			5500			
6000						
9.1 (XXS)	15.8	4000	5.64	〃	C	
		5500				
36	2	32	4000	1.69	〃	〃
	3	30	4000	2.47	〃	H
	4	28	4000	3.19	〃	〃
	5.5	25	4000	4.18	〃	〃
	8	20	4000	5.58	〃	〃
	10	16	4000	6.48	〃	C
38	1	36	4000	0.922	〃	〃
	1.2	35.6	4000	1.10	〃	〃
	1.5	35	4000	1.36	〃	〃
	2	34	4000	1.79	〃	〃
	3	32	4000	2.62	〃	H
	4	30	4000	3.39	〃	〃
	5	28	4000	4.11	〃	〃
	6	26	4000	4.78	〃	〃
40	8	22	4000	5.98	〃	〃
	1.5	37	4000	1.44	〃	C
	2	36	4000	1.89	〃	〃
	3	34	4000	2.77	〃	H
	4	32	4000	3.59	〃	〃
	5	30	6000	4.36	〃	〃
	6	28	4000	5.08	〃	〃

# シームレス管 / SUS304

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上
40	7.5	25	4000	6.07	TP	H
	8	24	4000	6.38	"	"
	10	20	4000	7.47	"	"
42.7 32A 1 1/4 B	1.65 (SCH5S)	39.4	4000	1.69	"	C
			5500			
	2	38.7	4000	2.03	"	"
	2.8 (SCH10S)	37.1	4000	2.78	"	H
			5500			
	3 (SCH20S)	36.7	4000	2.97	"	"
			5500			
			6000			
	3.6 (SCH40)	35.5	4000	3.51	"	"
			5500			C/H
			6000			H
	4.9 (SCH80)	32.9	4000	4.61	"	"
			5500			C/H
			6000			H
	6.4 (SCH160)	29.9	4000	5.79	"	"
5500			C/H			
6000			H			
8	26.7	5500	6.92	"	"	
9.1 (XXS)	24.5	4000	7.62	"	"	
		5500				
10	22.7	4000	8.15	"	"	
45	2	41	4000	2.14	"	C
	3	39	4000	3.14	"	H
			5000			
	4	37	4000	4.09	"	"
	5	35	4000	4.98	"	"
	7	31	4000	6.63	"	"
	8.5	28	4000	7.73	"	"
	10	25	6000	8.72	"	"
	12.5	20	4000	10.1	"	"
48.6 40A 1 1/2 B	1.65 (SCH5S)	45.3	4000	1.93	TP	C
			5500			
	2	44.6	4000	2.32	"	"
	2.8 (SCH10S)	43	4000	3.19	"	H
			5500			
			6000			
	3 (SCH20S)	42.6	4000	3.41	"	"
			5500			
			6000			
	3.7 (SCH40)	41.2	4000	4.14	"	"
			5500			
			6000			
	5.1 (SCH80)	38.4	4000	5.53	"	"
			5500			
			6000			
6	36.6	4000	6.4	"	"	
7.1 (SCH160)	34.4	4000	7.34	"	"	
		5500				
		6000				
10.2 (XXS)	28.2	4000	9.76	"	"	
		5500				
50.8	1.5	47.8	4000	1.84	"	C
	2	46.8	4000	2.43	"	"
	3	44.8	4000	3.57	"	H
	4	42.8	4000	4.66	"	"
	5	40.8	4000	5.70	"	"
	6.5	37.8	4000	7.17	"	"
	7.5	35.8	4000	8.09	"	"
	10.5	29.8	4000	10.5	"	"
	12.5	25.8	4000	11.9	"	"
	13.5	23.8	4000	12.5	"	"
	14.5	21.8	4000	13.1	"	"

# シームレス管 / SUS304

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上
52	3.5	45	4000	4.23	TP	H
	6	40	4000	6.88	〃	〃
	7.5	37	4000	8.31	〃	〃
	10	32	4000	10.5	〃	〃
	14	24	4000	13.3	〃	〃
54	2	50	4000	2.59	〃	C
	3	48	4000	3.81	〃	H
	3.5	47	4000	4.40	〃	〃
	4	46	4000	4.98	〃	〃
	5	44	4000	6.10	〃	〃
	6	42	4000	7.17	〃	〃
	9	36	6000	10.1	〃	〃
	12.5	29	6000	12.9	〃	〃
55	5	45	4000	6.23	〃	〃
56	3	50	4000	3.96	〃	〃
	6	44	4000	7.47	〃	〃
	8	40	4000	9.57	〃	〃
	10	36	4000	11.5	〃	〃
	14	28	6000	14.6	〃	〃
57	7.5	42	4000	9.2	〃	〃
58	10	38	4000	12.0	〃	〃
60	12.5	35	4000	14.8	〃	〃
60.5 50A 2B	1.65 (SCH5S)	57.2	4000	2.42	〃	C
			5500			
	2	56.5	4000	2.91	〃	〃
	2.8 (SCH10S)	54.9	4000	4.02	〃	H
			5500			
			6000			
	3	54.5	4000	4.30	〃	〃
			5500			
	3.5 (SCH20S)	53.5	4000	4.97	〃	〃
			5500			
6000						

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上
60.5 50A 2B	3.9 (SCH40)	52.7	4000	5.50	TP	H
			5500			
			6000			
	5.5 (SCH80)	49.5	4000	7.54	〃	〃
			5500			
			6000			
	6	48.5	6000	8.15	〃	〃
			6000			
	8.7 (SCH160)	43.1	4000	11.2	〃	〃
			5500			
			6000			
	10	40.5	6000	12.6	〃	〃
			6000			
11.1 (XXS)	38.3	4000	13.7	〃	〃	
		5500				
13	34.5	6000	15.4	〃	〃	
		6000				
15	30.5	6000	17.0	〃	〃	
		6000				
18	24.5	4000	19.1	〃	〃	
		4000				
62	7	48	4000	9.59	〃	〃
	8	46	4000	10.8	〃	〃
63.5	2	59.5	4000	3.06	〃	C
	3	57.5	4000	4.52	〃	H
	4	55.5	6000	5.93	〃	〃
	5	53.5	6100	7.29	〃	〃
	6	51.5	6000	8.59	〃	〃
	7	49.5	4000	9.85	〃	〃
	10	43.5	6000	13.3	〃	〃
	12	39.5	6000	15.4	〃	〃
65	2.0	61.0	4000	3.14	〃	C
			4000			
	3.0	59.0	4000	4.63	〃	H
			4000			
	4.0	57.0	6000	6.08	〃	〃
			6000			
5.0	55.0	4010	7.47	〃	〃	
		4000				
6.0	53.0	4000	8.82	〃	〃	

# シームレス管 / SUS304

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上
65	7.0	51.0	4000	10.1	TP	H
	8.5	48.0	6000	12.0	〃	〃
	10	45.0	4000	13.7	〃	〃
	12	41.0	4000	15.8	〃	〃
	13.5	38.0	6000	17.3	〃	〃
	15	35.0	6000	18.7	〃	〃
67	7.0	53.0	6000	10.5	〃	〃
	8.0	51.0	6000	11.8	〃	〃
	10	47.0	4000	14.2	〃	〃
68	8	52.0	4000	12.0	〃	〃
70	2.0	66.0	4000	3.39	〃	C
	3.0	64.0	4000	5.01	TK	H
	4.0	62.0	4000	6.58	TP	〃
	5.0	60.0	6000	8.10	〃	〃
	7.0	56.0	6100	11.0	〃	〃
	8.0	54.0	6000	12.4	〃	〃
	10	50.0	4000	14.9	〃	〃
	12.5	45.0	4000	17.9	〃	〃
	15	40.0	5000	20.6	〃	〃
71	4.0	63.0	4000	6.68	〃	〃
	7.5	56.0	6000	11.9	〃	〃
	13	45.0	5000	18.8	〃	〃
	17.5	36.0	4000	23.3	〃	〃
73	3.5	66.0	6000	6.06	〃	〃
	5.0	63.0	5500	8.47	〃	〃
	7.0	59.0	6000	11.5	〃	〃
	10	53.0	4000	15.7	〃	〃
	12.5	48.0	6000	18.8	〃	〃
	15	43.0	4000	21.7	〃	〃
75	10	55.0	4000	16.2	〃	〃
	12.5	50.0	5000	19.5	〃	〃
	15	45.0	4000	22.4	〃	〃
	17.5	40.0	5000	25.1	〃	〃

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上					
76.3 65 A 2 1/2 B	2.1 (SCH5S)	72.1	4000	3.88	TP	C					
			5500								
	3.0 (SCH10S)	70.3	4000	5.48	〃	H					
			5500								
			6000								
	3.5 (SCH20S)	69.3	4000	6.35	〃	〃					
			5500								
			6000								
	4.0	68.3	4000	7.20	〃	〃					
			5500								
	5.2 (SCH40)	65.9	4000	9.21	〃	〃					
			5500								
			6000								
	7.0 (SCH80)	62.3	4000	12.1	〃	〃					
			5500								
6000											
8.0	60.3	4000	13.6	〃	〃						
		5500									
		6000									
9.5 (SCH160)	57.3	4000	15.8	〃	〃						
		5500									
		6000									
80	2	76	4000	3.89	〃	C					
			6000								
			4				72	4000	7.57	〃	〃
			5				70	6000	9.3	〃	〃
			6				68	4000	11.1	〃	〃
80	3	74	6000	5.75	〃	H					
			4				72	4000	7.57	〃	〃
			5				70	6000	9.3	〃	〃
			6				68	4000	11.1	〃	〃
			10				60	6000	17.4	〃	〃
80	12.5	55	4000	21.0	〃	〃					
			6000								
			15				50	4000	24.3	〃	〃
			16				48	5000	25.5	〃	〃
80	17.5	45	5000	27.2	〃	〃					
			6000								



# シームレス管 / SUS304

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上
80	20	40	4000	29.9	TP	H
	25	30	4000	34.3	〃	〃
82	10	62	4000	17.9	〃	〃
	13	56	6000	22.3	〃	〃
	15	52	4000	25	〃	〃
85	8	69	6000	15.3	〃	〃
	10	65	6000	18.7	〃	〃
	12.5	60	6000	22.6	〃	〃
	15	55	4000	26.2	〃	〃
	20	45	4000	32.4	〃	〃
	22.5	40	L	35.0	TK	〃
	25	35	L	37.4	〃	〃
89.1 80A 3B	2.1 (SCH5S)	84.9	4000	4.55	TP	C
			5500			〃
	3 (SCH10S)	83.1	4000	6.43	〃	H
			5500			
			6000			
	4 (SCH20S)	81.1	4000	8.48	〃	〃
			5500			
			6000			
	5.5 (SCH40)	78.1	4000	11.5	〃	〃
			5500			
			6000			
	7.6 (SCH80)	73.9	4000	15.4	〃	〃
			5500			
	6000					
11.1 (SCH160)		66.9	4000	21.6	〃	〃
	5500					
	6000					
15.2 (XXS)	58.7	6000	28.0	〃	〃	
		6000				
90	10	70	5000	19.9	〃	〃
	13	64	4000	24.9	〃	〃
	13.5	63	4000	25.7	TK	〃

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上
90	15	60	4000	28.0	TP	H
	17.5	55	4500	31.6	TK	〃
	20	50	4000	34.9	TP	〃
	22.5	45	4000	37.8	TK	〃
92	25	40	6000	40.5	〃	〃
	11	70	5000	22.2	TP	〃
	16.8	58.4	4000	31.5	TK	〃
95	5	85	5500	11.2	TP	〃
	7.5	80	6000	16.3	〃	〃
	10	75	5000	21.2	〃	〃
	12.5	70	5000	25.7	〃	〃
	15	65	4000	29.9	〃	〃
	17.5	60	4000	33.8	TK	〃
	20	55	5000	37.4	〃	〃
	22.5	50	L	40.6	〃	〃
100	25	45	L	43.6	〃	〃
	10	80	5500	22.4	TP	〃
	12.5	75	3000	27.2	TK	〃
	15	70	4000	31.8	TP	〃
	18.5	63	3500	37.6	TK	〃
	20	60	L	39.9	〃	〃
	22	56	L	42.7	〃	〃
101.6 90A 3 1/2 B	2.1 (SCH5S)	97.4	4000	5.20	TP	C
			5500			〃
	3 (SCH10S)	95.6	4000	7.37	〃	H
			6000			
	4 (SCH20S)	93.6	4000	9.72	〃	〃
			6000			
	5.7 (SCH40)	90.2	4000	13.6	〃	〃
			6000			
	8.1 (SCH80)	85.4	4000	18.9	〃	〃
			6000			
12.7 (SCH160)	76.2	4000	28.1	〃	〃	
		6000				

# シームレス管 / SUS304

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上	外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上											
101.6 90A 3 1/2 B	15	71.6	4000	32.4	TP	H	114.3 100A 4B	11.1 (SCH120)	92.1	4000	28.5	TP	H											
			6000							5500														
	20	61.6	6000	40.7	"	"		13.5 (SCH160)	87.3	L	33.9	"	"											
			5000							6000														
103	10.5	82	4000	24.2	"	"		16	82.3	4000	39.2	"	"											
			6000							6000														
			105					5	95	6000	12.5	"	"	17.1 (XXS)	80.1	6000	41.4	"	"					
106	7	91	5000	17.1	"	"		20	74.3	6000	47.0	"	"											
			5000							6000														
			10							85				5000	23.7	"	"							
			10				86			5000				23.9	"	"								
			13				80			4000				30.1	"	"								
			17.5				71			L				38.6	TK	"								
108	13	82	4000	30.8	"	"	117	13.5	90	4000	34.8	TK	"											
			110				10	90	4000	24.9	TP	"												
			15						80	6000	35.5	TK	"											
110	20	70	4000	44.8	"	"	118	23.5	71	L	55.3	"	"											
			6000							3000				62										
			20					70	4000	44.8	"	"												
112	21	70	L	47.6	"	"	120	5	110	6000	14.3	"	"											
			24.5							63				L	53.4	"	"							
114.3 100A 4B	2.1 (SCH5S)	110.1	4000	5.87	TP	C		8	8	104	4500	22.3	"	"										
			5500								6000													
	3 (SCH10S)	108.3	108.3	4000	8.32	"		H	10	100	6000	27.4	"	"										
				5500							6000													
				6000					6000															
	4 (SCH20S)	106.3	106.3	4000	11.0	"		"	13	94	6000	34.6	"	"										
				5500							L				39.2									
				6000					6000															
	6 (SCH40)	102.3	102.3	4000	16.2	"	"	20	80	L	49.8	"	"											
				5500						L				59.2										
				6000				L	62.5															
	8.6 (SCH80)	97.1	97.1	4000	22.6	"	"	27	66	L	62.5	"	"											
5500				L						67.3														
6000				L				67.3																
125				5				115	6000	14.9	"	"	5	115	6000	14.9	"	"						
									5500						6000									
									10				105	6000	28.6	"	"	12.5	100	6000	35.0	"	"	
	6000	6000																						
	15	95	95		6000	41.1	"		"				15	95	6000	41.1	"	"						
					6000										6000									
17.5	90	90	L	46.9	"	"	17.5	90	L	46.9	"	"												
			6000						6000															
20	85	85	L	52.3	"	"	20	85	L	52.3	"	"												
			6000						6000															
22.5	80	80	L	57.4	"	"	22.5	80	L	57.4	"	"												
			6000						6000															
25	75	75	L	62.3	"	"	25	75	L	62.3	"	"												
			6000						6000															
27	71	71	L	65.9	"	"	27	71	L	65.9	"	"												
			6000						6000															
127	5	117	5000	15.2	"	"	127	5	117	5000	15.2	"	"											
			6000							6000														
			7							113				6000	20.9	"	"	7	113	6000	20.9	"	"	
														6000						6000				
			10							107				107	L	29.1	"	"	10	107	L	29.1	"	"
															6000						6000			
20	87	87	4000	53.3	"	"	20	87	4000	53.3	"	"												
			6000						6000															
27	73	73	L	67.3	"	"	27	73	L	67.3	"	"												
			6000						6000															

# シームレス管 / SUS304

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上
129	21	87	3000	56.5	TK	H
130	5	120	6000	15.6	〃	〃
	7	116	6000	21.4	〃	〃
	10	110	5000	29.9	〃	〃
	14	102	5000	40.5	〃	〃
	15	100	L	43.0	〃	〃
	16	98	L	45.4	〃	〃
132	13	106	3000	38.5	〃	〃
	16	100	4500	46.2	〃	〃
	21	90	L	58.1	〃	〃
	23.5	85	L	63.5	〃	〃
	26	80	L	68.7	〃	〃
	31	70	L	78.0	〃	〃
135	10	115	L	31.1	〃	〃
	15	105	L	44.8	〃	〃
	20	95	L	57.3	〃	〃
139.8 125A 5B	2.8 (SCH5S)	134.2	L	9.56	TP	C
	3.4 (SCH10S)	133	4000	11.6	〃	〃
			6000			
	5 (SCH20S)	129.8	4000	16.8	〃	H
			5500			
			6000			
	6.6 (SCH40)	126.6	4000	21.9	〃	〃
			5500			
			6000			
	9.5 (SCH80)	120.8	4000	30.8	〃	〃
5500						
6000						
12.7 (SCH120)	114.4	4000	40.2	〃	〃	
		6000				
15.9 (SCH160)	108	4000	49.1	〃	〃	
		6000				
20	99.8	6000	59.7	〃	〃	

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上	
140	10	120	5700	32.4	TK	H	
	14	112	4000	43.9	〃	〃	
	20	100	6000	59.8	〃	〃	
	25	90	L	71.6	〃	〃	
	27.5	85	L	77.1	〃	〃	
	30	80	L	82.2	〃	〃	
	35	70	L	91.5	〃	〃	
	145	10	125	6000	33.6	〃	〃
12.5		120	4000	41.3	〃	〃	
15		115	L	48.6	〃	〃	
20		105	L	62.3	〃	〃	
25		95	L	74.7	〃	〃	
30		85	L	85.9	〃	〃	
150		10	130	6000	34.9	〃	〃
	12.5	125	L	42.8	〃	〃	
	15	120	6000	50.4	〃	〃	
	17.5	115	L	57.8	〃	〃	
	20	110	L	64.8	〃	〃	
	22	106	L	70.1	〃	〃	
	25	100	L	77.8	〃	〃	
	30	90	L	89.7	〃	〃	
152.4	10	132.4	4600	35.5	TP	〃	
	154	10	134	L	35.9	TK	〃
	155	15	125	L	52.3	〃	〃
20		115	L	67.3	〃	〃	
26		103	L	83.5	〃	〃	
160	10	140	6000	37.4	〃	〃	
	12.5	135	L	45.9	〃	〃	
	15	130	L	54.2	〃	〃	
	20	120	L	69.7	〃	〃	
	24	112	L	81.3	〃	〃	

# シームレス管 / SUS304

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上
160	30	100	L	97.1	TK	H
	35	90	L	109	〃	〃
165.2 150A 6B	2.8 (SCH5S)	159.6	L	11.3	TP	C
	3.4 (SCH10S)		158.4	4000 6000	13.7	〃
	5 (SCH20S)	155.2	4000	20.0	〃	H
			5500			
			6000			
	7.1 (SCH40)	151	4000	28.0	〃	〃
			5500			
			6000			
	11 (SCH80)	143.2	4000	42.3	〃	〃
			5500			
6000						
14.3 (SCH120)	136.6	4000	53.8	〃	〃	
		6000				
18.2 (SCH160)	128.8	4000	66.6	〃	〃	
		6000				
21.9 (XXS)	121.4	6000	78.2	〃	〃	
170	10	150	6000	39.9	TK	〃
	15	140	6000	57.9	〃	〃
	20	130	L	74.7	〃	〃
	26	118	L	93.3	〃	〃
	32	106	L	110	〃	〃
	35	100	L	118	〃	〃
175	15	145	6000	59.8	〃	〃
180	10	160	6000	42.3	〃	〃
	12.5	155	6000	52.2	〃	〃
	15	150	L	61.7	〃	〃
	18	144	L	72.6	〃	〃
	20	140	L	79.7	〃	〃
	25	130	L	96.5	〃	〃
180	27.5	125	L	104	TK	H
	30	120	L	112	〃	〃
	35	110	L	126	〃	〃
	40	100	2001	139	〃	〃
185	10	165	2560	43.6	〃	〃
	20	145	L	82.2	〃	〃
190	10	170	6000	44.8	〃	〃
	12.5	165	L	55.3	〃	〃
	15	160	L	65.4	〃	〃
	17.5	155	L	75.2	〃	〃
	20	150	L	84.7	〃	〃
	22.5	145	L	93.9	〃	〃
190	25	140	L	103	〃	〃
	30	130	L	120	〃	〃
	190.7	7	176.7	6000	32.0	〃
200	10	180	L	47.3	〃	〃
	15	170	L	69.1	〃	〃
	20	160	L	89.7	〃	〃
	25	150	L	109	〃	〃
	30	140	L	127	〃	〃
	40	120	L	159	〃	〃
206	20	166	L	92.7	〃	〃
212	21	170	L	99.9	〃	〃
	27	158	L	124	〃	〃
	41	130	L	175	〃	〃
216.3 200A 8B	2.8 (SCH5S)	210.7	L	14.9	TP	C
	4 (SCH10S)		208.3	L	21.2	〃
	6.5 (SCH20S)	203.3	4000	34.0	〃	H
			5500			
			6000			
8.2 (SCH40)	199.9	4000	42.5	〃	〃	
		5500 6000				

# シームレス管 / SUS304

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上
216.3 200A 8B	12.7 (SCH80)	190.9	4000	64.4	TP	H
			5500			
			6000			
	18.2 (SCH120)	179.9	5500	89.8	"	"
			6000			
	23 (SCH160)	170.3	170.3	4000	111	"
6000						
224	33	150.3	L	151	"	"
	15	194	L	78.1	TK	"
	22	180	L	111	"	"
	32	160	L	153	"	"
236	42	140	L	190	"	"
	16	204	L	87.7	"	"
	23	190	L	122	"	"
	30	176	L	154	"	"
250	43	150	L	207	"	"
	15	220	L	87.8	"	"
	20	210	L	115	"	"
	25	200	L	140	"	"
	30	190	L	164	"	"
35	180	L	187	"	"	
254	24	206	L	138	"	"
255	24	207	L	138	"	"
267.4 250A 10B	3.4 (SCH5S)	260.6	L	22.4	TP	C
	4 (SCH10S)	259.4	L	26.2	"	"
	6.5 (SCH20S)	254.4	L	42.2	"	"
	9.3 (SCH40)	248.8	6000	59.8	"	H

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上
267.4 250A 10B	15.1 (SCH80)	237.2	6000	94.9	TP	H
	18.2	231	6000	113	"	"
	21.4 (SCH120)	224.6	6000	131	"	"
	28.6 (SCH160)	210.2	6000	170	"	"
275	37.5	200	2001	222	TK	"
318.5 300A 12B	4.5 (SCH10S)	309.5	L	35.2	TP	C
	6.5 (SCH20S)	305.5	L	50.5	"	"
	10.3 (SCH40)	297.9	6000	79.1	"	H
	17.4 (SCH80)	283.7	6000	131	"	"
	21.4	275.7	6000	158	"	"
	25.4 (SCH120)	267.7	6000	185	"	"
355.6 350A 14B	33.3 (SCH160)	251.9	6000	237	"	"
	11.1 (SCH40)	333.4	6000	95.3	"	"
	19 (SCH80)	317.6	6000	159	"	"
406.4 400A 16B	12.7 (SCH40)	381	6000	125	"	"
	21.4 (SCH80)	363.6	6000	205	"	"
	30.9 (SCH120)	344.6	6000	289	"	"