

シームレス管 / SUS304L

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上	外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上	
6	1.0	—	4000	0.125	TP	C	17.3 10A 3/8 B	2.3 (SCH40)	—	4000	0.859	TP	C	
			5500											
8	1.0	—	4000	0.174	"	"		3.2 (SCH80)	—	4000	1.12	"	"	
			5500											
10	1.0	—	4000	0.224	"	"		21.7 15A 1/2 B	1.65 (SCH5S)	—	4000	0.824	"	"
			5500											
10.5 6A 1/8 B	1.2 (SCH10S)	—	4000	0.278	"	"			2.1 (SCH10S)	—	4000	1.03	"	"
			5500											
	1.5 (SCH20S)	—	4000	0.336	"	"			2.5 (SCH20S)	—	4000	1.20	"	"
			5500											
1.7 (SCH40)	—	4000	0.373	"	"	2.8 (SCH40)	—		4000	1.32	"	"		
		5500												
12	1.0	—	4000	0.274	"	"	3.7 (SCH80)		—	4000	1.66	"	"	
			5500											
12.7	1.0	—	4000	0.291	"	"	4.7 (SCH160)	—	4000	1.99	"	"		
			5500											
13.8 8A 1/4 B	1.2 (SCH5S)	—	4000	0.377	"	"	27.2 20A 3/4 B	1.65 (SCH5S)	—	4000	1.05	"	"	
			5500											
	1.65 (SCH10S)	—	4000	0.499	"	"		2.1 (SCH10S)	—	4000	1.31	"	"	
			5500											
	2.0 (SCH20S)	—	4000	0.588	"	"		2.5 (SCH20S)	—	4000	1.54	"	"	
5500														
2.2 (SCH40)	—	4000	0.636	"	"	2.9 (SCH40)		—	4000	1.76	"	"		
		5500												
3.0 (SCH80)	—	4000	0.807	"	"	3.9 (SCH80)		—	4000	2.26	"	"		
		5500												
17.3 10A 3/8 B	1.2 (SCH5S)	—	4000	0.481	"	"	5.5 (SCH160)	—	4000	2.97	"	"		
			5500											
	1.65 (SCH10S)	—	4000	0.643	"	"	34 25A 1B	1.65 (SCH5S)	30.7	4000	1.33	"	"	
5500														
2.0 (SCH20S)	—	4000	0.762	"	"	2.8 (SCH10S)		28.4	4000	2.18	"	H		
		5500												

シームレス管 / SUS304L

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上
34 25A 1B	3.0 (SCH20S)	28	4000	2.32	TP	H
			5500	2.32	"	"
	3.4 (SCH40)	27.2	4000	2.59	"	"
			5500			
	4.5 (SCH80)	25	4000	3.31	"	"
			5500			
6000						
6.4 (SCH160)	21.2	4000	4.40	"	"	
42.7 32A 1 1/4 B	1.65 (SCH5S)	39.4	4000	1.69	"	C
	2.8 (SCH10S)	37.1	4000	2.78	"	H
			5500			H
	3.0 (SCH20S)	36.7	4000	2.97	"	"
			5500			
	3.6 (SCH40)	35.5	4000	3.51	"	"
5500						
4.9 (SCH80)	32.9	4000	4.61	"	"	
		5500				
6.4 (SCH160)	29.9	4000	5.79	"	"	
		5500				
48.6 40A 1 1/2 B	1.65 (SCH5S)	45.3	4000	1.93	"	C
			5500			C
	2.8 (SCH10S)	43	4000	3.19	"	H
			5500			C/H
	3.0 (SCH20S)	42.6	4000	3.41	"	H
			5500			H
3.7 (SCH40)	41.2	4000	4.14	"	"	
		5500				
5.1 (SCH80)	38.4	4000	5.53	"	"	
		5500				
7.1 (SCH160)	34.4	4000	7.34	"	"	
		5500				

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上
60.5 50A 2B	2.8 (SCH10S)	54.9	4000	4.02	TP	H
			5500			H
	3.5 (SCH20S)	53.5	4000	4.97	"	"
			5500			
	3.9 (SCH40)	52.7	4000	5.50	"	"
			5500			
5.5 (SCH80)	49.5	4000	7.54	"	"	
		5500				
8.7 (SCH160)	43.1	4000	11.2	"	"	
		5500				
76.3 65A 2 1/2 B	3.0 (SCH10S)	70.3	4000	5.48	"	"
			5500			"
	3.5 (SCH20S)	69.3	4000	6.35	"	"
			5500			
	5.2 (SCH40)	65.9	4000	9.21	"	"
			5500			
7.0 (SCH80)	62.3	4000	12.1	"	"	
		5500				
9.5 (SCH160)	57.3	5500	15.8	"	"	
		5500				
89.1 80A 3B	3.0 (SCH10S)	83.1	4000	6.43	"	"
			5500			"
	4.0 (SCH20S)	81.1	4000	8.48	"	"
			5500			
	5.5 (SCH40)	78.1	4000	11.5	"	"
			5500			
7.6 (SCH80)	73.9	4000	15.4	"	"	
		5500				
11.1 (SCH160)	66.9	5500	21.6	"	"	
		5500				
101.6 90A 3 1/2 B	4.0 (SCH20S)	93.6	5500	9.73	"	"
			5500			"
	5.7 (SCH40)	90.2	4000	13.6	"	"
5500						

