

シームレス管 / SUS316

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上
3	0.5	-	2000	0.0313	TP	C
	1.0		2000	0.0501		
4	0.5	-	2000	0.0439	"	"
	1.0		4000	0.0752		
5	0.5	-	2000	0.0564	"	"
			4000			
	1.0	-	2000	0.100	"	"
			4000			
6	0.5	-	2000	0.0689	"	"
	1.0	-	4000	0.125		
	1.5	-	4000	0.169	"	"
	2.0	-	4000	0.201		
6.35	0.5	-	2000	0.0733	"	"
			4000			
	1.0	-	4000	0.134	"	"
			1.5	-		
8	0.5	-	2000	0.094	"	"
			4000			
	1.0	-	2000	0.176	"	"
			4000			
	1.5	-	4000	0.244	"	"
2.0	-	4000	0.301	"	"	
9.53	1.0	-	4000	0.214	"	"
	1.5	-	4000	0.302	"	"
10	1.0	-	2000	0.226	"	"
			4000			
	1.2	-	4000	0.265	"	"
	1.5	-	4000	0.395	"	"
	2.0	-	4000	0.401	"	"
10.5 6A 1/8 B	1.0 (SCH5S)	-	4000	0.238	"	"
	1.2 (SCH10S)	-	4000	0.280	"	"

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上
10.5 6A 1/8 B	1.5 (SCH20S)	-	4000	0.338	TP	C
			2000			
	1.7 (SCH40)	-	4000	0.375	"	"
			5500			
2.4 (SCH80)	-	4000	0.487	"	"	
		5500				
11	0.5	-	4000	0.132	"	"
12	1.0	-	2000	0.276	"	"
			4000			
	1.5	-	4000	0.395	"	"
			2.0	-		
12.7	1.0	-	4000	0.293	"	"
	1.24	-	4000	0.356	"	"
	1.5	-	4000	0.421	"	"
	1.65	-	4000	0.457	"	"
13	1.0	-	4000	0.301	"	"
13.8 8A 1/4 B	1.2 (SCH5S)	-	4000	0.379	"	"
			1.65 (SCH10S)			
	2.0 (SCH20S)	-	4000	0.592	"	"
			5500			
	2.2 (SCH40)	-	4000	0.640	"	"
5500						
3.0 (SCH80)	-	4000	0.812	"	"	
		5500				
14	1.0	-	4000	0.326	"	"
	2.0	-	4000	0.602	"	"
15	1.0	-	4000	0.351	"	"
	1.5	-	4000	0.508	"	"
	2.0	-	4000	0.652	"	"
16	0.5	-	4000	0.194	"	"
	1.0	-	4000	0.376	"	"

シームレス管 / SUS316

29

継目無ステンレス鋼管

SUS316

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上	外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上	
16	1.5	—	4000	0.545	TP	C	22	1.0	—	4000	0.527	TP	C	
	2.0	—	4000	0.702										
17.3 10A 3/8 B	1.2 (SCH5S)	—	4000	0.484	"	"	25	1.0	—	4000	0.602	"	"	
			5500	0.647				—	4000	0.884				
	1.65 (SCH10S)	—	4000	0.647	"	"		2.0	—	4000	1.15	"	"	
			5500					0.767	—	4000	1.65			
	2.0 (SCH20S)	—	4000	0.767	"	"		25.4	1.2	—	4000	0.728	"	"
			5500						0.865	—	4000	0.899		
2.3 (SCH40)	—	4000	0.865	"	"	2.0	—		4000	1.17	"	"		
		5500				1.13	—		4000	1.68				
3.2 (SCH80)	—	4000	1.13	"	"	27.2 20A 3/4 B	1.65 (SCH5S)		—	4000	1.06	"	"	
		5500					1.32		—	5500	1.55			
18	1.0	—	4000	0.426	"		"	2.1 (SCH10S)	—	4000	1.55	"	"	
	1.5	—	4000	0.621				—	5500					
	2.0	—	4000	0.802				—	5500					
19	1.0	—	4000	0.451	"		"	2.5 (SCH20S)	—	4000	1.77	"	"	
	1.5	—	4000	0.658		—		5500						
	2.0	—	4000	0.852		—		5500						
20	1.0	—	4000	0.476	"	"	2.9 (SCH40)	—	4000	2.28	"	"		
	1.5	—	4000	0.696			—	5500						
	2.0	—	4000	0.903			—	5500						
	3.0	—	4000	1.28			—	5500						
21.7 15A 1/2 B	1.65 (SCH5S)	—	4000	0.829	"	"	30	2.0	26	4000	1.40	"	"	
			5500					1.03	—	4000	2.03			
	2.1 (SCH10S)	—	4000	1.03	"	"		5.0	20	4000	3.13	"	"	
			5500					1.20	—	4000	3.38			
	2.5 (SCH20S)	—	4000	1.20	"	"		32	2.0	28	4000	1.50	"	"
			5500						1.33	—	4000	2.18		
	2.8 (SCH40)	—	4000	1.33	"	"			3.0	26	4000	2.81	"	"
			5500						1.67	—	4000	3.38		
3.7 (SCH80)	—	4000	1.67	"	"	34 25A 1B	1.65 (SCH5S)	30.7	4000	1.34	"	"		
		5500					2.00	—	4000	1.60				
4.7 (SCH160)	—	4000	2.00	"	"		2.0	30	4000	2.19	"	"		
		5500					2.19	—	5500					

シームレス管 / SUS316

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上
34 25A 1B	3.0 (SCH20S)	28	4000	2.33	TP	C/H
			5500			
	3.4 (SCH40)	27.2	4000	2.61	"	H
			5500			C/H
	4.5 (SCH80)	25	4000	3.33	"	"
			5500			
			6000			
	6.4 (SCH160)	21.2	4000	4.43	"	"
			5500			
	9.1 (XXS)	15.8	4000	5.68	"	C
			6000			
	38	2.0	34	4000	1.81	"
3.0		32	4000	2.63	"	H
4.0		30	4000	3.4	"	"
42.7 32A 1 1/4 B	1.65 (SCH5S)	39.4	4000	1.70	"	C
			5500			
	2.8 (SCH10S)	37.1	4000	2.80	"	"
			5500			C/H
	3.0 (SCH20S)	36.7	4000	2.99	"	H
			5500			
	3.6 (SCH40)	35.5	4000	3.53	"	"
			5500			
	4.9 (SCH80)	32.9	4000	4.64	"	"
			5500			
	6.4 (SCH160)	29.9	4000	5.82	"	"
			5500			
45	8	29	5000	7.42	TK	"
48.6 40A 1 1/2 B	1.65 (SCH5S)	45.3	4000	1.94	TP	C
			5500			
	2.8 (SCH10S)	43	4000	3.22	"	H
			5500			C/H
	3.0 (SCH20S)	42.6	4000	3.43	"	H
			5500			
3.7 (SCH40)	41.2	4000	4.16	"	"	
		5500				

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上
48.6 40A 1 1/2 B	5.1 (SCH80)	38.4	4000	5.56	TP	H
			5500			
	7.1 (SCH160)	34.4	4000	7.39	"	"
			5500			
	10.2 (XXS)	28.2	6000	9.82	"	"
	50.8	3.0	44.8	4000	3.60	"
60.5 50A 2B	1.65 (SCH5S)	57.2	4000	2.43	"	C
			5500			
	2.0	56.5	4000	2.93	"	"
			5500			
	2.8 (SCH10S)	54.9	4000	4.05	"	H
			5500			C/H
	3.0	54.5	4000	4.32	"	H
	3.5 (SCH20S)	53.5	4000	5.00	"	"
			5500			
	3.9 (SCH40)	52.7	4000	5.53	"	"
			5500			
			6000			
5.5 (SCH80)	49.5	4000	7.58	"	C/H	
		5500			H	
8.7 (SCH160)	43.1	4000	11.3	"	"	
		5500				
11.1 (XXS)	38.3	5500	13.7	"	"	
70	10.0	50	5000	15.0	"	"
	12.5	45	5500	18.0	"	"
	15.0	40	4000	20.7	"	"
76.3 65A 2 1/2 B	2.1 (SCH5S)	72.1	4000	3.91	"	C
			5500			
	3.0 (SCH10S)	70.3	4000	5.51	"	H
			5500			
	3.5 (SCH20S)	69.3	4000	6.39	"	"
			5500			

シームレス管 / SUS316

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上	外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上							
76.3 65A 2 1/2 B	5.2 (SCH40)	65.9	4000	9.27	TP	H	101.6 90A 3 1/2 B	3.0 (SCH10S)	95.6	5500	7.42	TP	H							
			5500																	
	7.0 (SCH80)	62.3	4000	12.2	"	"		4.0 (SCH20S)	93.6	6000	9.79	"	"							
			5500																	
	9.5 (SCH160)	57.3	4000	15.9	"	"		5.7 (SCH40)	90.2	5500	13.7	"	"							
			5500																	
6000																				
14.0 (XXS)	48.3	4000	21.9	"	"	8.1 (SCH80)	85.4	6000	19.0	"	"									
		5500																		
80	10.0	60	6000	17.5	"	"	114.3 100A 4B	2.1 (SCH5S)	110.1	4000	5.91	"	C							
	15.0	50	4000	24.4	"	"		3.0 (SCH10S)	108.3	4000	8.37	"	"							
85	12.5	60	4000	22.7	"	"	5500													
	15.0	55	4000	26.3	"	"	6000			H										
89.1 80A 3B	2.1 (SCH5S)	84.9	4000	4.58	"	C	4.0 (SCH20S)	106.3	4000	11.1	"	"								
	3.0 (SCH10S)	83.1	4000	6.48	"	H			5500											
			4.0 (SCH20S)				81.1	4000	8.53	"	"	6.0 (SCH40)	102.3	4000	16.3	"	"			
	5500																			
	5.5 (SCH40)	78.1		4000	11.5	"		"				8.6 (SCH80)	97.1	4000				22.8	"	"
				5500																
	7.6 (SCH80)	73.9	4000	15.5	"	"	11.1 (SCH120)	92.1	4000	28.7	"	"								
			5500																	
			11.1 (SCH160)				66.9	4000	21.7				"	"	13.5 (SCH160)	87.3	5500	34.1	"	"
								5500												
	90	15.0	60	4000	28.2	"	"	120	20	80	3400	50.2	TK	"						
				5500																
135	10	115	3250	31.3	"	"	139.8 125A 5B	3.4 (SCH10S)	133	4000	11.6	TP	C							
			20							95				2600	57.7	"	"			

シームレス管 / SUS316

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上	
139.8 125A 5B	5.0 (SCH20S)	129.8	4000	16.9	TP	C/ H	
			5500				
	6.6 (SCH40)	126.6	4000	22.0	"	H	
			5500				
	9.5 (SCH80)	120.8	4000	31.0	"	"	
			6000				
	12.7 (SCH120)	114.4	6000	40.5	"	"	
	15.9 (SCH160)	108	4000	49.4	"	"	
			6000				
	165.2 150A 6B	3.4 (SCH10S)	158.4	4000	13.8	"	C
				5500			
5.0 (SCH20S)		155.2	4000	20.1	"	C/ H	
			5500				
7.1 (SCH40)		151	4000	28.1	"	H	
			5500				
			6000				
11.0 (SCH80)		143.2	4000	42.5	"	"	
			5500				
14.3 (SCH120)		136.6	6000	54.1	"	"	
18.2 (SCH160)		128.8	6000	67.1	"	"	
216.3 200A 8B		4.0 (SCH10S)	208.3	L	21.3	"	C
	6.5 (SCH20S)	203.3	4000	34.2	"	H	
			5500				
			6000				
	8.2 (SCH40)	199.9	4000	42.8	"	"	
			5500				
			6000				

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上
216.3 200A 8B	12.7 (SCH80)	190.9	4000	64.8	TP	H
			5500			
			6000			
	18.2 (SCH120)	179.9	4000	90.4	"	"
			6000			
	23.0 (SCH160)	170.3	4000	111	"	"
	267.4 250A 10B	9.3 (SCH40)	248.8	6000	60.2	"
	15.1 (SCH80)	237.2	6000	95.5	"	"
318.5 300A 12B	10.3 (SCH40)	297.9	6000	79.6	"	"
	17.4 (SCH80)	283.7	6000	131	"	"