

シームレス管 / SUS316L

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上	外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上
6	0.5	—	4000	0.069	TP	C	3.0 (SCH80)	—	4000	0.812	TP	C	
	1.0	—	4000	0.125	〃	〃							
	1.5	—	4000	0.169	〃	〃	15	2.0	—	4000	0.652	〃	〃
6.35	1.0	—	4000	0.134	〃	〃	16	1.0	—	4000	0.376	〃	〃
8	0.5	—	4000	0.094	〃	〃		1.5	—	4000	0.545	〃	〃
	1.0	—	4000	0.175	〃	〃		2.0	—	4000	0.702	〃	〃
	1.5	—	4000	0.244	〃	〃	3.0	—	4000	0.978	〃	〃	
	2.0	—	4000	0.301	〃	〃	17.3 10A 3/8 B	1.2 (SCH5S)	—	4000	0.484	〃	〃
9.53	1	—	4000	0.214	〃	〃		1.65 (SCH10S)	—	4000	0.647	〃	〃
	1.5	—	4000	0.320	〃	〃		5500					
	2.0	—	4000	0.401	〃	〃		2.0 (SCH20S)	—	4000	0.767	〃	〃
10.5 6A 1/8 B	1.0 (SCH5S)	—	4000	0.238	〃	〃	5500						
	1.2 (SCH10S)	—	4000	0.280	〃	〃	2.3 (SCH40)	—	4000	0.865	〃	〃	
	1.5 (SCH20S)	—	4000	0.338	〃	〃	5500						
	1.7 (SCH40)	—	4000	0.375	〃	〃	3.2 (SCH80)	—	4000	1.13	〃	〃	
	5500												
	2.0	—	4000	0.426	〃	〃	20	1.0	—	4000	0.476	〃	〃
2.4 (SCH80)	—	4000	0.487	〃	〃	1.5		—	4000	0.696	〃	〃	
5500													
12	1.0	—	4000	0.276	〃	〃	21.7 15A 1/2 B	1.65 (SCH5S)	—	4000	0.829	〃	〃
	1.5	—	4000	0.395	〃	〃		5000					
	2.0	—	4000	0.501	〃	〃		2.1 (SCH10S)	—	4000	1.03	〃	〃
5500													
12.7	1.0	—	4000	0.293	〃	〃	5500						
	2.5 (SCH20S)	—	4000	1.20	〃	〃	2.8 (SCH40)	—	4000	1.33	〃	〃	
	5500												
13.8 8A 1/4 B	1.2 (SCH5S)	—	4000	0.379	〃	〃	3.7 (SCH80)	—	4000	1.67	〃	〃	
	1.65 (SCH10S)	—	4000	0.503	〃	〃	5500						
	2.0 (SCH20S)	—	4000	0.592	〃	〃	4.7 (SCH160)	—	4000	2.00	〃	〃	
	5500												
2.2 (SCH40)	—	4000	0.640	〃	〃	7.5 (XXS)	—	5500	2.67	〃	〃		
5500													

シームレス管 / SUS316L

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上
22	1.0	—	4000	0.526	TP	C
	1.5	—	4000	0.771	”	”
25.4	2	—	4000	1.17	”	”
27.2 20 A 3/4 B	1.65 (SCH5S)	—	4000	1.06	”	”
			5500	1.32	”	”
	2.1 (SCH10S)	—	4000	1.55	”	”
			5500			
	2.5 (SCH20S)	—	4000	1.77	”	”
			5500			
	2.9 (SCH40)	—	4000	2.28	”	”
			5500			
3.9 (SCH80)	—	4000	2.99	”	”	
		5500				
5.5 (SCH160)	—	4000	2.99	”	”	
		5500				
30	1.0	28.0	4000	0.727	”	”
	3.0	24.0	4000	2.03	”	”
34 25 A 1 B	1.65 (SCH5S)	30.7	4000	1.34	”	”
			6000			
	2.8 (SCH10S)	28.4	4000	2.19	”	”
			5500			
			6000			
	3.0 (SCH20S)	28.0	4000	2.33	”	H
			5500			
	3.4 (SCH40)	27.2	4000	2.61	”	”
			5500			
			6000			
4.5 (SCH80)	25.0	4000	3.33	”	”	
		5500				
		6000				
6.4 (SCH160)	21.2	4000	4.43	”	C/H	
		5500				

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上
42.7 32 A 1 1/4 B	9.1 (XXS)	15.8	4000	5.68	TP	C
			5500			
	1.65 (SCH5S)	39.4	4000	1.70	”	”
			5500	2.80	”	H
	2.8 (SCH10S)	37.1	4000	2.99	”	”
			5500			
	3.0 (SCH20S)	36.7	4000	3.53	”	”
			5500			
	3.6 (SCH40)	35.5	4000	4.64	”	”
			5500			
4.9 (SCH80)	32.9	4000	5.82	”	”	
		5500				
6.4 (SCH160)	29.9	4000	5.82	”	C/H	
		5500				
6000	29.9	4000	5.82	”	C/H	
		5500				
48.6 40 A 1 1/2 B	1.65 (SCH5S)	45.3	4000	1.94	”	C
			5500	3.22	”	H
	2.8 (SCH10S)	43.0	4000	3.43	”	”
			5500			
	3.0 (SCH20S)	42.6	4000	4.17	”	”
			5500			
	3.7 (SCH40)	41.2	4000	5.56	”	”
			5500			
	5.1 (SCH80)	38.4	4000	7.39	”	”
			5500			
7.1 (SCH160)	34.4	4000	9.82	”	”	
		5500				
10.2 (XXS)	28.2	4000	9.82	”	”	
		5500				

シームレス管 / SUS316L

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上	外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上				
60.5 50 A 2 B	1.65 (SCH5S)	57.2	4000	2.43	TP	C	80	15	50	4000	24.4	TP	H				
			4000							4000				30.1	〃	〃	
	2.8 (SCH10S)	54.9	4000	4.05	〃	H		89.1 80 A 3 B	2.1 (SCH5S)	84.9	4000	4.58	〃	C			
			5500														
			6000														
	3.5 (SCH20S)	53.5	4000	5.00	〃	〃		89.1 80 A 3 B	3.0 (SCH10S)	83.1	4000	6.48	〃	H			
			5500														
			6000														
	3.9 (SCH40)	52.7	4000	5.53	〃	〃		89.1 80 A 3 B	4.0 (SCH20S)	81.1	4000	8.53	〃	〃			
			5500														
			6000														
	5.5 (SCH80)	49.5	4000	7.58	〃	〃		89.1 80 A 3 B	5.5 (SCH40)	78.1	4000	11.5	〃	〃			
5500																	
6000																	
8.7 (SCH160)	43.1	4000	11.3	〃	〃	89.1 80 A 3 B	7.6 (SCH80)	73.9	4000	15.5	〃	〃					
		5500															
		6000															
63.5	6.5	50.5	6000	9.29	〃	〃	101.6 90 A 3 1/2 B	2.1 (SCH5S)	97.4	4000	5.24	〃	C				
65	15	35.0	6000	18.8	〃	〃				3.0 (SCH10S)				95.6	4000	7.42	〃
71	10.5	50.0	6000	15.9	〃	〃	5.7 (SCH40)	90.2	4000		13.7	〃	〃				
76.3 65 A 2 1/2 B	2.1 (SCH5S)	72.1	4000	3.91	〃	C			8.1 (SCH80)	85.4				4000	19.0	〃	〃
			5500														
	3.0 (SCH10S)	70.3	4000	5.51	〃	H	12.7 (SCH160)	76.2			4000	28.3	〃	〃			
			5500														
3.5 (SCH20S)	69.3	4000	6.39	〃	〃	106	25	56	2400	51.1	〃	〃					
		5500															
5.2 (SCH40)	65.9	4000	9.27	〃	〃	114.3 100 A 4 B	2.1 (SCH5S)	110.1	4000	5.91	〃	C					
		5500															
		6000															
7.0 (SCH80)	62.3	4000	12.2	〃	〃	114.3 100 A 4 B	3.0 (SCH10S)	108.3	4000	8.37	〃	H					
		5500															
		6000															
9.5 (SCH160)	57.3	4000	15.9	〃	〃	114.3 100 A 4 B	3.0 (SCH10S)	108.3	4000	8.37	〃	H					
		5500															
15	46.3	4000	23.1	〃	〃	114.3 100 A 4 B	3.0 (SCH10S)	108.3	6000	8.37	〃	H					

シームレス管 / SUS316L

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上
114.3 100 A 4 B	4.0 (SCH20S)	106.3	4000	11.1	TP	H
			5500			
	6.0 (SCH40)	102.3	4000	16.3	"	"
			5500			
			6000			
	8.6 (SCH80)	97.1	4000	22.8	"	"
			5500			
			6000			
	11.1 (SCH120)	92.1	4000	28.7	"	"
			6000			
13.5 (SCH160)	87.3	6000	34.1	"	"	
17.1 (XXS)	80.1	6000	41.7	"	"	
139.8 125 A 5 B	2.8 (SCH5S)	134.2	4000	9.62	"	C
			L			
	3.4 (SCH10S)	133.0	4000	11.6	"	"
			6000			
	5.0 (SCH20S)	129.8	4000	16.9	"	C/H
			5500			
	6.6 (SCH40)	126.6	4000	22.0	"	H
			5500			
			6000			
	9.5 (SCH80)	120.8	4000	31.0	"	"
5500						
6000						
12.7 (SCH120)	114.4	5500	40.5	"	"	
15.9 (SCH160)	108.0	6000	49.4	"	"	
160	14	132	6000	57.2	"	"
165.2 150 A 6 B	2.8 (SCH5S)	159.6	L	11.4	"	C
	3.4 (SCH10S)	158.4	6000	13.8	"	"

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上
165.2 150 A 6 B	5.0 (SCH20S)	155.2	4000	20.1	TP	C/H
			5500			"
			6000			"
	7.1 (SCH40)	151.0	4000	28.1	"	H
			5500			
			6000			
	11 (SCH80)	143.2	4000	42.5	"	"
			5500			
			6000			
	14.3 (SCH120)	136.6	5500	54.1	"	"
18.2 (SCH160)	128.8	6000	67.1	"	"	
190	15	160	6000	65.8	"	"
190.7	11	168.7	4000	49.6	"	"
216.3 200 A 8 B	4.0 (SCH10S)	208.3	L	21.3	"	C
	6.5 (SCH20S)	203.3	4000	34.2	"	H
			5500			
			6000			
	8.2 (SCH40)	199.9	4000	42.8	"	"
			5500			
			6000			
	12.7 (SCH80)	190.9	4000	64.8	"	"
	6000					
18.2 (SCH120)	179.9	6000	90.4	"	"	
23 (SCH160)	170.3	4000	111	"	"	

シームレス管 / SUS316L

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上
267.4 250 A 110 B	4.0 (SCH10S)	259.4	L	26.4	TP	C
	6.5 (SCH20S)	254.4	L	42.5	”	”
	9.3 (SCH40)	248.8	6000	60.2	”	H
	15.1 (SCH80)	237.2	6000	95.5	”	”
	28.6 (SCH160)	210.2	6000	171	”	”
318.5 300 A 12 B	4.5 (SCH10S)	309.5	L	35.4	”	C
	6.5 (SCH20S)	305.5	L	50.8	”	”
	10.3 (SCH40)	297.9	6000	79.6	”	H
	17.4 (SCH80)	283.7	6000	131	”	”
	25.4 (SCH120)	267.7	6000	187	”	”
	33.3 (SCH160)	251.9	6000	238	”	”
355.6 350 A 14 B	11.1 (SCH40)	333.4	6000	95.9	”	”
	19 (SCH80)	317.6	6000	160	”	”
	27.8 (SCH120)	300.0	6000	228	”	”
406.4 400 A 16 B	12.7 (SCH40)	381.0	6000	125	”	”
	21.4 (SCH80)	363.6	6000	207	”	”