

シームレス管 / SUS310S

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上
6	1.0	—	4000	0.125	TP	C
8	1.0	—	4000	0.175	"	"
10	1.0	—	4000	0.226	"	"
10.5 6A 1/8 B	1.5 (SCH20S)	—	4000	0.338	"	"
	1.7 (SCH40)	—	4000	0.375	"	"
	2.4 (SCH80)	—	4000	0.487	"	"
12	1.0	—	4000	0.276	"	"
	1.5	—	4000	0.395	"	"
	2.0	—	4000	0.501	"	"
13.8 8A 1/4 B	1.2 (SCH5S)	—	4000	0.379	"	"
	1.65 (SCH10S)	—	4000	0.503	"	"
	2.0 (SCH20S)	—	4000	0.592	"	"
	2.2 (SCH40)	—	4000	0.640	"	"
	3.0 (SCH80)	—	4000	0.812	"	"
15	2.0	—	4000	0.652	"	"
17.3 10A 3/8 B	1.65 (SCH10S)	—	4000	0.647	"	"
	2.0 (SCH10S)	—	4000	0.767	"	"
	2.3 (SCH40)	—	4000	0.87	"	"
		—	5500			
3.2 (SCH80)	—	4000	1.13	"	"	

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上
21.7 15A 1/2 B	2.1 (SCH10S)	—	4000	1.03	TP	C
			5500			
	2.5 (SCH20S)	—	4000	1.20	"	"
			5500			
	2.8 (SCH40)	—	4000	1.33	"	"
			5500			
3.7 (SCH80)	—	4000	1.67	"	"	
		5500				
4.7 (SCH160)	—	4000	2.00	"	"	
		5500				
27.2 20A 3/4 B	2.1 (SCH10S)	—	4000	1.32	"	"
			5500			
	2.5 (SCH20S)	—	4000	1.55	"	"
			5500			
	2.9 (SCH40)	—	4000	1.77	"	"
			5500			
6000						
3.9 (SCH80)	—	4000	2.28	"	"	
		5500				
		6000				
5.5 (SCH160)	—	4000	2.99	"	"	
		5500				
34 25A 1 B	2.8 (SCH10S)	28.4	4000	2.19	"	"
			5500			
	3 (SCH20S)	28	4000	2.33	"	H
			5500			
	3.4 (SCH40)	27.2	4000	2.61	"	"
5500						
6000						
4.5 (SCH80)	25	4000	3.33	"	"	
		5500				
		6000				
6.4 (SCH160)	—	21.2	6000	4.43	"	"

シームレス管 / SUS310S

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上	外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上		
42.7 32A 1 1/4 B	2.8 (SCH10S)	37.1	5500	2.80	TP	C	60.5 50 A 2 B	5.5 (SCH80)	49.5	4000	7.58	TP	H		
			5500												
			6000												
	3.0 (SCH20S)	36.7	4000	2.99	"	H		8.7 (SCH160)	43.1	4000	11.3	"	"		
			4500												
			5500												
	3.6 (SCH40)	35.5	4000	3.53	"	"		76.3 65 A 2 1/2 B	3.0 (SCH10S)	70.3	4000	5.51	"	"	
			5500												
			6000												
	4.9 (SCH80)	32.9	4000	4.64	"	"		3.5 (SCH20S)	69.3	4000	6.39	"	"		
			5500												
			6000												
6.4 (SCH160)	29.9	4000	5.82	"	"	5.2 (SCH40)	65.9	4000	9.27	"	"				
		5500													
		6000													
48.6 40 A 1 1/2 B	2.8 (SCH10S)	43	4000	3.22	"	C	89.1 80 A 3 B	3.0 (SCH10S)	83.1	4000	6.48	"	"		
			5500												
	3.0 (SCH20S)	42.6	4000	3.43	"	H		4.0 (SCH20S)	81.1	4000	8.53	"	"		
			5500												
	3.7 (SCH40)	41.2	4000	4.17	"	"		5.5 (SCH40)	78.1	4000	11.5	"	"		
			5500												
	5.1 (SCH80)	38.4	4000	5.56	"	"		7.6 (SCH80)	73.9	4000	15.5	"	"		
			5500												
	7.1 (SCH160)	34.4	4000	7.39	"	"		11.1 (SCH160)	66.9	4000	21.7	"	"		
			5500												
	60.5 50 A 2 B	2.8 (SCH10S)	54.9	4000	4.05	"		C/H	101.6 90 A 3 1/2 B	4.0 (SCH20S)	93.6	5000	9.79	"	"
				5500											
3.5 (SCH20S)		53.5	4000	5.00	"	H	5.7 (SCH40)	90.2		4000	13.7	"	"		
			5500												
3.9 (SCH40)		52.7	4000	5.53	"	"	6000	6000							
			5500												
6000															

シームレス管 / SUS310S

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上
101.6 90 A 3 1/2 B	8.1 (SCH80)	85.4	6000	19.0	TP	H
	12.7 (SCH160)	76.2	4000	28.3	"	"
114.3 100 A 4 B	3.0 (SCH10S)	108.3	4000	8.4	"	"
			6000			
	4.0 (SCH20S)	106.3	4000	11.1	"	"
			6000			
	6.0 (SCH40)	102.3	4000	16.3	"	"
			5500			
			6000			
	8.6 (SCH80)	97.1	4000	22.8	"	"
6000						
11.1 (SCH120)	92.1	6000	28.7	"	"	
13.5 (SCH160)	87.3	5000	34.1	"	"	
139.8 125 A 5 B	5.0 (SCH20S)	129.8	4000	16.9	"	"
			5500			
	6.6 (SCH40)	126.6	4000	22.0	"	"
			6000			
	9.5 (SCH80)	120.8	5000	31.0	"	"
12.7 (SCH120)	114.4	6000	40.5	"	"	
15.9 (SCH160)	108	6000	49.4	"	"	
165.2 150 A 6 B	5.0 (SCH20S)	155.2	4000	20.1	"	"
			5000			
	7.1 (SCH40)	151	4000	28.1	"	"
			5500			
		6000				

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	規格	仕上
165.2 150 A 6 B	11 (SCH80)	143.2	4000	42.5	TP	H
			5500			
	14.3 (SCH120)	136.6	5500	54.1	"	"
	18.2 (SCH160)	128.8	4000	67.1	"	"
			L			
216.3 200 A 8 B	12.7 (SCH80)	190.9	5400	64.8	"	"