

ASTM/ASME A312/SA312 / TP316/316L

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	仕上
13.72 8A 1/4 B	1.65 (SCH10S)	10.42	6000	0.499	C
	2.24 (SCH40S)	9.24	6000	0.645	"
17.15 10A 3/8 B	2.31 (SCH40S)	12.53	6000	0.859	"
21.34 15A 1/2 B	2.11 (SCH10S)	17.12	6000	1.02	"
	2.77 (SCH40S)	15.8	6000	1.29	"
	3.73 (SCH80)	13.88	6000	1.65	"
26.67 20A 3/4 B	2.11 (SCH10S)	22.45	6000	1.30	"
	2.87 (SCH40S)	20.93	6000	1.71	"
	3.91 (SCH80)	18.85	6000	2.23	"
33.4 25A 1B	2.77 (SCH10S)	27.86	6000	2.13	"
	3.38 (SCH40S)	26.64	6000	2.54	H
	4.55 (SCH80)	24.3	6000	3.29	"
	6.35 (SCH160)	20.7	6000	4.31	"
42.16 32A 1 1/4 B	2.77 (SCH10S)	36.62	6000	2.74	"
	3.56 (SCH40S)	35.04	6000	3.45	"
	4.85 (SCH80)	32.46	6000	4.54	"
	6.35 (SCH160)	29.46	6000	5.70	"

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	仕上
48.26 40A 1 1/2 B	2.77 (SCH10S)	42.72	6000	3.16	H
	3.68 (SCH40S)	40.9	6000	4.11	"
	5.08 (SCH80)	38.1	6000	5.50	"
	7.14 (SCH160)	33.98	6000	7.36	"
60.33 50A 2B	2.77 (SCH10S)	54.79	6000	4.00	"
	3.91 (SCH40S)	52.51	6000	5.53	"
	5.54 (SCH80)	49.25	6000	7.61	"
	8.74 (SCH160)	42.85	6000	11.3	"
	73.03 65A 2 1/2 B	3.05 (SCH10S)	66.93	6000	5.35
88.9 80A 3B	5.16 (SCH40S)	62.71	6000	8.78	"
	7.01 (SCH80)	59.01	6000	11.6	"
	7.62 (SCH80)	73.66	6000	15.5	"
114.3 100A 4B	3.05 (SCH10S)	108.2	6000	8.51	"
	6.02 (SCH40S)	102.26	6000	16.3	"
	8.56 (SCH80)	97.18	6000	22.7	"

※一部、規格：シングル、鋼種：シングル品あり

ASTM/ASME A312/SA312 / TP316/316L

外径	肉厚 (SCH)	内径	長さ	質量 (kg/m)	仕上
141.3 125A 5B	3.4 (SCH10S)	134.5	6000	11.8	C
	6.55 (SCH40S)	128.2	6000	22.1	H
	9.52 (SCH80)	122.26	6000	31.5	〃
168.28 150A 6B	3.4 (SCH10S)	161.48	6000	14.1	C
	7.11 (SCH40S)	154.06	6000	28.7	H
	10.97 (SCH80)	146.34	6000	43.3	〃
219.08 200A 8B	3.76 (SCH10S)	211.56	6000	20.3	C
	8.18 (SCH40S)	202.72	6000	43.3	H
	12.7 (SCH80)	193.68	6000	65.7	〃
273.05 250A 10B	9.27 (SCH40S)	254.51	6000	61.3	〃
323.85 300A 12B	10.31 (SCH40S)	303.23	6000	81.0	〃

※一部、規格：シングル、鋼種：シングル品あり