

溶接管 / SUS304

外径	肉厚 (SCH)	長さ	質量 (kg/m)	規格
10.5 6A 1/8 B	1.5 (SCH20S)	4000	0.336	TPA
	2.0 (SCH40)	4000	0.423	"
13.8 8A 1/4 B	1.2 (SCH5S)	4000	0.377	"
	1.5 (SCH10S)	4000	0.460	"
	2.0 (SCH20S)	4000	0.588	"
	2.5 (SCH40)	4000	0.704	"
17.3 10A 3/8 B	1.2	4000	0.481	"
	1.5	4000	0.590	"
	2.0 (SCH10S/20S)	4000	0.762	"
		6000		
	2.5 (SCH40)	4000	0.922	"
3.0	4000	1.07	"	
21.7 15A 1/2 B	1.5 (SCH5S)	4000	0.755	"
	2.0 (SCH10S)	4000	0.981	"
		6000		
	2.5 (SCH20S)	4000	1.20	"
		6000		
	3.0 (SCH40)	4000	1.40	"
6000				
25.4	1.5	4000	0.893	"
	2.0	4000	1.17	"
	3.0	4000	1.67	"

外径	肉厚 (SCH)	長さ	質量 (kg/m)	規格
27.2 20A 3/4 B	1.5 (SCH5S)	4000	0.960	TPA
	2.0 (SCH10S)	4000	1.26	"
		6000		
	2.5 (SCH20S)	4000	1.54	"
6000				
3.0 (SCH40)	4000	1.81	"	
	6000			
30	3.0	4000	2.02	"
34 25A 1B	1.5	4000	1.21	"
	2.0 (SCH5S)	4000	1.59	"
		6000		
	2.5 (SCH10S)	6000	1.96	"
	3.0 (SCH20S)	4000	2.32	"
		6000		
3.5 (SCH40)	4000	2.66	"	
	6000			
4.0	4000	2.99	"	
	6000			
	6000			
38	1.5	4000	1.36	"
	2.0	4000	1.79	"
	3.0	4000	2.62	"
42.7 32A 1 1/4 B	1.5	4000	1.54	"
	2.0 (SCH5S)	4000	2.03	"
		6000		
	3.0 (SCH10S/20S)	4000	2.97	"
		6000		
	3.5 (SCH40)	4000	3.42	"
6000				
4.0	4000	3.86	"	
	6000			

溶接管 / SUS304

外径	肉厚 (SCH)	長さ	質量 (kg/m)	規格	外径	肉厚 (SCH)	長さ	質量 (kg/m)	規格		
48.6 40A 1 1/2 B	1.5	4000	1.76	TPA	76.3 65A 2 1/2 B	4.0	4000	7.20	TPA		
	2.0 (SCH5S)	4000	2.32	"		6000					
		3.0 (SCH10S/20S)				4000	3.41	"			
	6000										
	3.5	4000	3.93	"		5.0 (SCH40)	4000	8.88	"		
		6000									
	4.0 (SCH40)	4000	4.44	"		5.2	4000	9.21	"		
		6000									
	5.1	4000	5.53	"		7.0 (SCH80)	4000	12.1	"		
		6000									
	50.8	2.0	4000	2.43		"	89.1 80A 3 B	2.0 (SCH5S)	4000	4.34	"
		3.0	4000	3.57		"		6000			
60.5 50A 2 B	1.5	4000	2.21	"	3.0 (SCH10S)	4000		6.43	"		
	2.0 (SCH5S)	4000	2.91	"		6000					
3.0 (SCH10S)		4000			4.30	"		4.0 (SCH20S)	4000	8.48	"
	6000										
3.5 (SCH20S)	4000	4.97	"	5.5 (SCH40)	4000	11.5		"			
	6000										
4.0 (SCH40)	4000	5.63	"	7.6	4000	15.4		"			
	6000										
5.5 (SCH80)	4000	7.54	"	2.0	4000	4.96		"			
	6000										
63.5	2.0	4000	3.06	"	3.0 (SCH10S)	4000	7.37	"			
	76.3 65A 2 1/2 B	2.0 (SCH5S)	4000	3.70		"			6000		
3.0 (SCH10S)			4000		5.48		"	4.0 (SCH20S)	4000	9.73	"
	6000										
3.5 (SCH20S)	4000	6.35	"	5.7	4000	13.6	"				
	6000										
60.5 50A 2 B	2.0 (SCH5S)	4000	2.91	"	6.0 (SCH40)	4000	14.3	"			
		6000									
3.0 (SCH10S)	4000	5.48	"	8.1	4000	18.9	"				
	6000										
101.6 90A 3 1/2 B	2.0	4000	4.96	"	3.0 (SCH10S)	4000	7.37	"			
		6000									
4.0 (SCH20S)	4000	5.63	"	4.0 (SCH20S)	4000	9.73	"				
	6000										
5.5 (SCH80)	4000	7.54	"	5.7	4000	13.6	"				
	6000										
63.5	2.0	4000	3.06	"	6.0 (SCH40)	4000	14.3	"			
	76.3 65A 2 1/2 B	2.0 (SCH5S)	4000	3.70		"			6000		
3.0 (SCH10S)			4000		5.48		"	8.1	4000	18.9	"
	6000										
3.5 (SCH20S)	4000	6.35	"	5.7	4000	13.6	"				
	6000										
114.3 100A 4 B	2.0	4000	5.60	"	3.0 (SCH10S)	4000	8.32	"			
		6000									
3.0 (SCH10S)	4000	6.35	"	5.7	4000	13.6	"				
	6000										

溶接管 / SUS304

外径	肉厚 (SCH)	長さ	質量 (kg/m)	規格
114.3 100A 4B	4.0 (SCH20S)	4000	11.0	TPA
		6000		
	5.0	4000	13.6	"
		6000		
	6.0 (SCH40)	4000	16.2	"
		6000		
8.6	4000	22.6	"	
	6000			
139.8 125A 5B	3.0 (SCH5S)	4000	10.2	"
		6000		
	3.5 (SCH10S)	4000	11.9	"
		6000		
	4.0	4000	13.5	"
		6000		
5.0 (SCH20S)	4000	16.8	"	
	6000			
6.6	4000	21.9	"	
	6000			
9.5	4000	30.8	"	
	165.2 150A 6B	3.0 (SCH5S)	4000	12.1
6000				
3.5 (SCH10S)		4000	14.1	"
		6000		
4.0		4000	16.1	"
		6000		
5.0 (SCH20S)	4000	20.0	"	
	6000			
7.1	4000	28.0	"	
	6000			
11.0	4000	42.3	"	

外径	肉厚 (SCH)	長さ	質量 (kg/m)	規格
190.7	3.0	4000	14.0	TPA
	4.0	4000	18.6	"
	6.0	4000	27.6	"
216.3 200A 8B	3.0 (SCH5S)	4000	15.9	"
		6000		
	4.0 (SCH10S)	4000	21.2	"
		6000		
	5.0	4000	26.3	"
		6000		
6.5 (SCH20S)	4000	34.0	"	
	6000			
8.2	4000	42.5	"	
	6000			
12.7	4000	64.4	"	
	6000			
267.4 250A 10B	3.0	4000	19.8	"
		6000		
	3.5 (SCH5S)	4000	23.0	"
		6000		
	4.0 (SCH10S)	4000	26.2	"
		6000		
5.0	4000	32.7	"	
	6000			
6.5 (SCH20S)	4000	42.2	"	
	6000			
9.3	4000	59.8	"	
	6000			
15.1	4000	94.9	"	
	6000			
21.4	6000	131	"	
	28.6	4000	170	"
6000				

溶接管 / SUS304

外径	肉厚 (SCH)	長さ	質量 (kg/m)	規格	外径	肉厚 (SCH)	長さ	質量 (kg/m)	規格
318.5 300A 12B	3.0	4000	23.6	TPA	406.4 400A 16B	12.7 (SCH40)	4000	125	TPYSA
		6000							
	4.0 (SCH5S)	4000	31.3	"		21.4	6000	205	"
		6000							
	4.5 (SCH10S)	4000	35.2	"		4.0	4000	45.2	"
		6000							
	6.5 (SCH20S)	4000	50.5	"		4.5 (SCH5S)	4000	50.7	"
		6000							
	10.3	4000	79.1	"		5.0 (SCH10S)	4000	56.3	"
		6000							
17.4	4000	131	"	8.0 (SCH20S)	4000	89.5	"		
	6000								
25.4	4000	185	"	14.3 (SCH40)	4000	158	"		
	6000								
33.3	4000	237	"	508 500A 20B	4.0	4000	50.2	"	
	6000								
355.6 350A 14B	4.0 (SCH5S)	4000	35.0		TPYSA	5.0 (SCH5S)	4000	62.6	"
		6000							
5.0 (SCH10S)	4000	43.7	"		5.5 (SCH10S)	4000	68.8	"	
	6000								
6.0	4000	52.3	"		6.0	4000	75.0	"	
	6000								
8.0 (SCH20S)	4000	69.3	"		9.5 (SCH20S)	4000	118	"	
	6000								
11.1 (SCH40)	4000	95.3	"	15.1 (SCH40)	4000	185	"		
	6000								
19.0	4000	159	"	406.4 400A 16B	4.0	4000	40.1	"	
	6000								
4.5 (SCH5S)	4000	45.1	"		4.5 (SCH5S)	4000	45.1	"	
	6000								
5.0 (SCH10S)	4000	50.0	"		5.0 (SCH10S)	4000	50.0	"	
	6000								
6.0	4000	59.8	"		6.0	4000	59.8	"	
	6000								
8.0 (SCH20S)	4000	79.4	"		8.0 (SCH20S)	4000	79.4	"	
	6000								