

溶接管 / SUS304L

外径	肉厚 (SCH)	長さ	質量 (kg/m)	規格
17.3 10A 3/8 B	2.0 (SCH10S/SCH20S)	4000	0.762	TPA
	2.5 (SCH40)	4000	0.922	"
21.7 15A 1/2 B	2.0 (SCH10S)	4000	0.981	"
	2.5 (SCH20S)	4000	1.20	"
	3.0 (SCH40)	4000	1.40	"
27.2 20A 3/4 B	2.0 (SCH10S)	4000	1.26	"
	2.5 (SCH20S)	4000	1.54	"
	3.0 (SCH40)	4000	1.81	"
34 25A 1B	1.5	4000	1.21	"
	2.0 (SCH5S)	4000	1.59	"
	3.0 (SCH20S)	4000	2.32	"
	3.5 (SCH40)	4000	2.66	"
42.7 32A 1 1/4 B	3.0 (SCH10S/SCH20S)	4000	2.97	"
	3.5 (SCH40)	4000	3.42	"
48.6 40A 1 1/2 B	2.0 (SCH5S)	4000	2.32	"
	3.0 (SCH10S/SCH20S)	4000	3.41	"
	4.0 (SCH40)	4000	4.44	"

外径	肉厚 (SCH)	長さ	質量 (kg/m)	規格
60.5 50A 2B	2.0 (SCH5S)	4000	2.91	TPA
	3.0 (SCH10S)	4000	4.30	"
	3.5 (SCH20S)	4000	4.97	"
	4.0 (SCH40)	4000	5.63	"
76.3 65A 2 1/2 B	2.0 (SCH5S)	4000	3.70	"
	3.0 (SCH10S)	4000	5.48	"
	3.5 (SCH20S)	4000	6.35	"
	5.2	4000	9.21	"
89.1 80A 3B	2.0 (SCH5S)	4000	4.34	"
	3.0 (SCH10S)	4000	6.43	"
	4.0 (SCH20S)	4000	8.48	"
	5.5 (SCH40)	4000	11.5	"
114.3 100A 4B	3.0 (SCH10S)	4000	8.32	"
	4.0 (SCH20S)	4000	11.0	"
	6.0 (SCH40)	4000	16.2	"
139.8 125A 5B	3.0 (SCH5S)	4000	10.2	"
	3.5 (SCH10S)	4000	11.9	"

溶接管 / SUS304L

外径	肉厚 (SCH)	長さ	質量 (kg/m)	規格
139.8 125A 5B	5.0 (SCH20S)	4000	16.8	TPA
165.2 150A 6B	3.0 (SCH5S)	4000	12.1	〃
	3.5 (SCH10S)	4000	14.1	〃
	5.0 (SCH20S)	4000	20.0	〃
	7.1	4000	28.0	〃
216.3 200A 8B	4.0 (SCH10S)	4000	21.2	〃
	6.5 (SCH20S)	4000	34.0	〃
	8.2	4000	42.5	〃