

溶接管 / SUS316

外径	肉厚 (SCH)	長さ	質量 (kg/m)	規格
13.8 8A 1/4 B	1.5 (SCH10S)	11	0.463	TPA
	2.0 (SCH20S)	4000	0.592	"
	3.0 (SCH80)	4000	0.812	"
17.3 10A 3/8 B	2.0 (SCH10S/20S)	4000	0.767	"
	2.5 (SCH40)	4000	0.928	"
	3.0	4000	1.08	"
21.7 15A 1/2 B	1.5 (SCH5S)	4000	0.76	"
	2.0 (SCH10S)	4000	0.988	"
	2.5 (SCH20S)	4000	1.20	"
	3.0 (SCH40)	4000	1.41	"
		6000		
27.2 20A 3/4 B	1.5 (SCH5S)	4000	0.966	"
	2.0 (SCH10S)	4000	1.26	"
	2.5 (SCH20S)	4000	1.55	"
	3 (SCH40)	4000	1.82	"
		6000		
34 25A 1B	2.0 (SCH5S)	4000	1.60	"
	3.0 (SCH20S)	4000	2.33	"
		6000		
3.5 (SCH40S)	4000	2.68	"	

外径	肉厚 (SCH)	長さ	質量 (kg/m)	規格
34 25A 1B	4.0	4000	3.01	TPA
42.7 32A 1 1/4 B	2.0 (SCH5S)	4000	2.04	"
	3.0 (SCH10S/20S)	4000	2.99	"
	3.5 (SCH40)	4000	3.44	"
	4.0	4000	3.88	"
48.6 40A 1 1/2 B	2.0 (SCH5S)	4000	2.34	"
	3.0 (SCH10S/20S)	4000	3.43	"
		6000		
	3.5	4000	3.96	"
	4.0 (SCH40)	4000	4.47	"
5.1	4000	5.56	"	
60.5 50A 2B	2.0 (SCH5S)	4000	2.93	"
	3.0 (SCH10S)	4000	4.33	"
		6000		
	3.5 (SCH20S)	4000	5.00	"
	4.0 (SCH40)	4000	5.67	"
	5.5 (SCH80)	4000	7.58	"
76.3 65A 2 1/2 B	2.0 (SCH5S)	4000	3.73	"
	3.0 (SCH10S)	4000	5.51	"
		6000		

溶接管 / SUS316

外径	肉厚 (SCH)	長さ	質量 (kg/m)	規格	外径	肉厚 (SCH)	長さ	質量 (kg/m)	規格	
76.3 65A 2 1/2 B	3.5 (SCH20S)	4000	6.39	TPA	139.8 125A 5B	3.0 (SCH5S)	4000	10.3	TPA	
	4.0	4000	7.25	〃		3.5 (SCH10S)	4000	12.0	〃	
	5.0 (SCH40)	4000	8.94	〃		4.0	4000	13.6	〃	
	5.2	4000	9.27	〃		5.0 (SCH20S)	4000	16.9	〃	
	7.0 (SCH80)	4000	12.2	〃		6.6	4000	22.0	〃	
89.1 80A 3B	2.0 (SCH5S)	4000	4.37	〃		9.5	4000	31.0	〃	
	3.0 (SCH10S)	4000 6000	6.48	〃		165.2 150A 6B	3.0 (SCH5S)	4000	12.2	〃
	4.0 (SCH20S)	4000	8.53	〃			3.5 (SCH10S)	4000	14.2	〃
	5.5 (SCH40)	4000	11.5	〃			4.0	4000	16.2	〃
	7.6	4000	15.5	〃			5.0 (SCH20S)	4000	20.1	〃
101.6 90A 3 1/2 B	2.0	4000	4.99	〃	7.1		4000	28.1	〃	
101.6 90A 3 1/2 B	3.0 (SCH10S)	4000	7.42	〃	11	4000	42.5	〃		
	4.0 (SCH20S)	4000	9.79	〃	216.3 200A 8B	3.0 (SCH5S)	4000	16.0	〃	
	114.3 100A 4B	2.0	4000	5.63		〃	4.0 (SCH10S)	4000	21.3	〃
3.0 (SCH10S)		4000 6000	8.37	〃		6.5 (SCH20S)	4000	34.2	〃	
4.0 (SCH20S)		4000	11.1	〃		8.2	4000	42.8	〃	
6.0 (SCH40)		4000	16.3	〃		12.7	4000	64.8	〃	
8.6		4000	22.8	〃						

溶接管 / SUS316

外径	肉厚 (SCH)	長さ	質量 (kg/m)	規格
267.4 250A 10B	3.0	4000	19.9	TPA
	4.0 (SCH10S)	4000	26.4	〃
	6.5 (SCH20S)	4000	42.5	〃
	9.3	4000	60.2	〃
	15.1	4000	95.5	〃
318.5 300A 12B	4.0 (SCH5S)	4000	31.5	〃
	4.5 (SCH10S)	4000	35.4	〃
	6.5 (SCH20S)	4000	50.8	〃
	10.3	4000	79.6	〃
355.6 350A 14B	4.0 (SCH5S)	4000	35.3	TPYSA
	5.0 (SCH10S)	4000	43.9	〃
	8.0 (SCH20S)	4000	69.7	〃
	11.1 (SCH40)	4000	95.9	〃
406.4 400A 16B	4.0	4000	40.4	〃
	5.0 (SCH10S)	4000	50.3	〃
	8.0 (SCH20S)	4000	79.9	〃
	12.7 (SCH40)	4000	125.4	〃
457.2 400A 18B	4.0	4000	45.4	〃

外径	肉厚 (SCH)	長さ	質量 (kg/m)	規格
457.2 400A 18B	5.0 (SCH10S)	4000	56.7	TPYSA
	8.0 (SCH20S)	4000	90.1	〃
508 500A 20B	5.0 (SCH5S)	4000	63.1	〃
	9.5 (SCH20S)	4000	119	〃