

溶接管 / SUS316L

外径	肉厚 (SCH)	長さ	質量 (kg/m)	規格	外径	肉厚 (SCH)	長さ	質量 (kg/m)	規格		
13.8 8A 1/4 B	2.0 (SCH20S)	4000	0.592	TPA	42.7 32A 1 1/4 B	3.5 (SCH40)	4000	3.44	TPA		
	4.0					4000				3.88	〃
17.3 10A 3/8 B	2.0 (SCH10S/20S)	4000	0.767	〃	48.6 40A 1 1/2 B	2.0 (SCH5S)	4000	2.34	〃		
	2.5 (SCH40)					4000				3.43	〃
	3.0										
21.7 15A 1/2 B	2.0 (SCH10S)	4000	0.988	〃	60.5 50A 2 B	3.0 (SCH10S)	4000	4.33	〃		
	2.5 (SCH20S)					4000				5.00	〃
	3.0 (SCH40)										
27.2 20A 3/4 B	3.5	4000	1.41	〃	76.3 65A 2 1/2 B	2.0 (SCH5S)	4000	3.73	〃		
	2.0 (SCH10S)					4000				5.51	〃
	2.5 (SCH20S)										
	3.0 (SCH40)					6000				7.25	〃
34 25A 1 B	1.5 (SCH5S)	4000	1.22	〃	76.3 65A 2 1/2 B	3.0 (SCH10S)	4000	8.94	〃		
	2.0 (SCH10S)					4000				1.82	〃
	2.5 (SCH20S)										
	3.0 (SCH40)					6000				3.01	〃
42.7 32A 1 1/4 B	1.5	4000	1.60	〃	76.3 65A 2 1/2 B	3.5 (SCH40)	4000	2.04	〃		
	2.0 (SCH5S)					4000				2.33	〃
	3.0 (SCH 20S)										
	3.5 (SCH40)					6000				2.99	〃

溶接管 / SUS316L

外径	肉厚 (SCH)	長さ	質量 (kg/m)	規格
76.3 65A 2 1/2 B	5.2	4000	9.27	TPA
	7.0 (SCH80)	4000	12.2	"
89.1 80A 3 B	2.0 (SCH5S)	4000	4.37	"
	3.0 (SCH10S)	4000	6.48	"
		6000		
	4.0 (SCH20S)	4000	8.53	"
	5.5 (SCH40)	4000	11.5	"
	7.6	4000	15.5	"
101.6 90A 3 1/2 B	2.0	4000	4.99	"
	3.0 (SCH10S)	4000	7.42	"
	4.0 (SCH20S)	4000	9.79	"
	5.7	4000	13.7	"
114.3 100A 4 B	2.0	4000	5.63	"
	3.0 (SCH10S)	4000	8.37	"
		6000		
	4.0 (SCH20S)	4000	11.1	"
	6.0 (SCH40)	4000	16.3	"
	8.6	4000	22.8	"

外径	肉厚 (SCH)	長さ	質量 (kg/m)	規格
139.8 125A 5 B	3.0 (SCH5S)	4000	10.3	TPA
	3.5 (SCH10S)	4000	12.0	"
	4.0	4000	13.6	"
	5.0 (SCH20S)	4000	16.9	"
	6.6	4000	22.0	"
	9.5	4000	31.0	"
165.2 150A 6 B	3.0 (SCH5S)	4000	12.2	"
	3.5 (SCH10S)	4000	14.2	"
	4.0	4000	16.2	"
	5.0 (SCH20S)	4000	20.1	"
	7.1	4000	28.1	"
	11	4000	42.5	"
216.3 200A 8 B	3.0 (SCH5S)	4000	16.0	"
	4.0 (SCH10S)	4000	21.3	"
	6.5 (SCH20S)	4000	34.2	"
	8.2	4000	42.8	"
	12.7	4000	64.8	"

溶接管 / SUS316L

61

溶接ステンレス鋼管

SUS316L

外径	肉厚 (SCH)	長さ	質量 (kg/m)	規格	外径	肉厚 (SCH)	長さ	質量 (kg/m)	規格
267.4 250A 10B	3.0	4000	19.9	TPA	406.4 400A 16B	8.0 (SCH20S)	4000	79.9	TPYSA
	4.0 (SCH10S)	4000	26.4	”		12.7 (SCH40)	4000	125	”
	6.5 (SCH20S)	4000	42.5	”	457.2 450A 18B	4.0	4000	45.4	”
	9.3	4000	60.2	”		5.0 (SCH10S)	4000	56.7	”
	15.1	4000	237.2	”		8.0 (SCH20S)	4000	90.1	”
318.5 300A 12B	3.0	4000	23.7	”	14.3 (SCH40)	4000	159	”	
	4.0 (SCH5S)	4000	31.5	”	508 500A 20B	5.0 (SCH5S)	4000	63.1	”
	4.5 (SCH10S)	4000	35.4	”		9.5 (SCH20S)	4000	119	”
	6.5 (SCH20S)	4000	50.8	”					
	10.3	4000	79.6	”					
	17.4	4000	131	”					
355.6 350A 14B	4.0 (SCH5S)	4000	35.3	TPYSA					
	5.0 (SCH10S)	4000	43.9	”					
	8.0 (SCH20S)	4000	69.7	”					
	11.1 (SCH40)	4000	95.9	”					
406.4 400A 16B	4.0	4000	40.4	”					
	5.0 (SCH10S)	4000	50.3	”					