

溶接管 / SUS310S

外径	肉厚 (SCH)	長さ	質量 (kg/m)	規格
21.7 15A 1/2 B	3.0 (SCH40)	4000	1.41	TPA
27.2 20A 3/4 B	3.0 (SCH40)	4000	1.82	〃
34 25A 1B	3.0 (SCH20S)	4000	2.33	〃
42.7 32A 1 1/4 B	3.0 (SCH10S/20S)	4000	2.99	〃
48.6 40A 1 1/2 B	3.0 (SCH10S/20S)	4000	3.43	〃
60.5 50A 2B	3.0 (SCH10S)	4000	4.33	〃
76.3 65A 2 1/2 B	3.0 (SCH10S)	4000	5.51	〃
89.1 80A 3B	3.0 (SCH10S)	4000	6.48	〃
114.3 100A 4B	3.0 (SCH10S)	4000	8.37	〃
216.3 200A 8B	4.0 (SCH10S)	4000	21.3	〃
	6.5 (SCH20S)	4000	34.2	〃
	8.2	4000	42.8	〃

外径	肉厚 (SCH)	長さ	質量 (kg/m)	規格
267.4 250A 10B	4.0 (SCH10S)	4000	26.4	TPA
	6.5 (SCH20S)	4000	42.5	〃
	9.3	4000	60.2	〃
318.5 300A 10B	6.5 (SCH20S)	4000	50.8	〃
	10.3	4000	79.0	〃